


Part Number : FF01-524/SP-XX  
 Description : 524nm blocking edge short-pass filter


Optical Spectrum



GF Technology Sdn. Bhd (270452-U)  
 Plot 108, Phase 4, Hilir Sg. Keluang 5,  
 11900 Bayan Lepas,  
 Penang, Malaysia

Phone : +604-641 3106 / 3107 / 3109  
 Fax : +604-641 2950  
 Web : [www.gf-technology.com](http://www.gf-technology.com)  
 Email : [info@gf-technology.com](mailto:info@gf-technology.com)

Blocking Band Spectrum



Your actual filter spectrum may slightly differ from the typical spectrum above but is certified to meet the optical specifications noted below

Part Number	Size	Price	Remarks
FF01-524/SP-23.5D	23.5mm x 1mm	Please email us for quotation	Round shape, unmounted
FF01-524/SP-25D	25mm x 1mm	Please email us for quotation	Round shape, unmounted
FF01-524/SP-35x35	35mm x 35mm x 1mm	Please email us for quotation	unmounted
FF01-524/SP-50x50	50mm x 50mm x 1mm	Please email us for quotation	unmounted

Optical Specifications

Specifications	Value
Transmission Band 1	$T_{abs} > 93\%$ 443 - 514 nm
Edge Wavelength	515 nm
Blocking Band 1	$OD_{abs} > 4$ 524 – 800 nm

**Part Number : FF01-524/SP-XX**

**Description : 524nm blocking edge short-pass filter**

**General Filter Specifications**

Specifications	Value
Angle of Incidence	0 ± 5 degrees

**Physical Filter Specifications (applies to standard sized parts)**

Specifications	FF01-524/SP-23.5D	FF01-524/SP-25D	FF01-524/SP-35x35	FF01-524/SP-50x50
Transverse Dimension	23.5 mm Diameter	25 mm Diameter	L = 35 mm , W = 35 mm	L = 50 mm , W = 50 mm
Transverse tolerance	± 0.1 mm			
Filter thickness (unmounted)	1.0 mm			
Filter thickness tolerance (unmounted)	± 0.1 mm			
Clear Aperture	Full	Full	Full	Full
Scratch-Dig	60 - 40			